



[...It's all go in the kitchen!

It's great that with CONVOTHERM, you don't need cool-down time and the programmes can be changed directly.
This leaves you enough time for creating, garnishing and arranging. And I enjoy my work all the more!]



OB SERIES

Technical data

OEB/OGB

Option of electrical or gas connection



CONVOTHERM OEB/OGB 6.10



CONVOTHERM OEB/OGB 6.20

Appliance type	Combi steamer, tabletop	Combi steamer, tabletop
Appliance dimensions (W x D x H) mm	932 x 805 x 852	1217 x 1027 x 895
Weight electrical/gas (ConvoClean +20 kg)	155/175 kg	215/235 kg
Shelves		
1/1 GN	7	14
2/1 GN	–	7
EN=Euronorm 400 mm x 600 mm	5	12
Number of plates (Plated Banqueting System)	20 plates	42 plates
GN shelf spacing mm	68	68
Installation conditions OEB		
Connection value: electrical connection (3N~ 400V 50/60Hz)	11.8 kW	19.9 kW
Convection power output	10.5 kW	18.9 kW
Steam generator power output	9.9 kW	16.5 kW
Rated current (3N~ 400V 50/60Hz)	15.7 A	26.6 A
Installation conditions OGB		
Connection value: electrical connection (1N~ 230V 50/60Hz)	1.4 kW	1.4 kW
Connection value: electrical connection (3N~ 400V 50/60Hz)	1.2 kW	1.2 kW
Convection power output: gas connection	12 kW	20 kW
Steam generator power output	12 kW	18 kW
Rated current (1N~ 230V 50/60Hz)	4.9 A	4.9 A
Rated current (3N~ 400V 50/60Hz)	2.9 A	2.9 A



CONVOTHERM OEB/OGB 10.10

CONVOTHERM OEB/OGB 10.20

CONVOTHERM OEB/OGB 12.20

Combi steamer, tabletop

932 x 805 x 1120

175/200kg

11

–

7

32 plates

68

19.9 kW

18.9 kW

16.5 kW

26.6 A

1.4 kW

1.2 kW

20 kW

18 kW

4.9 A

2.9 A

Combi steamer, tabletop

1217 x 1027 x 1120

245/280 kg

22

11

18

63 plates

68

34.4 kW

33.0 kW

26.4 kW

48.0 A

1.8 kW

1.5 kW

35 kW

30 kW

6.2 A

3.6 A

Combi steamer, floor model

1232 x 1055 x 1416

314*/342* kg

24

12

10

59 or 74 plates

67

34.4 kW

33.0 kW

29.7 kW

48.0 A

1.8 kW

1.5 kW

40 kW

35 kW

6.2 A

3.6 A

* incl. trolley



CONVOTHERM OEB/OGB 20.10



CONVOTHERM OEB/OGB 20.20



Combi steamer, floor model

947 x 855 x 1952
315*/344* kg

20

–

17

50 or 61 plates

67

39.7 kW

37.8 kW

29.7 kW

52.8 A

2.6 kW

2.2 kW

40 kW

30 kW

9.1 A

5.1 A

* incl. trolley

Combi steamer, floor model

1232 x 1055 x 1952
414*/458* kg

40

20

17

98 or 122 plates

67

68.6 kW

66.0 kW

39.6 kW

95.4 A

2.7 kW

2.2 kW

70 kW

35 kW

9.4 A

5.4 A

* incl. trolley